ADVANTAGE PLUS

sheetfed blanket

OFFSET PRINTING BLANKETS



ADVANTAGE PLUS

Designed and formulated for wide range of sheet-fed presses for printing on all kinds of inks and paper/carton stocks

APPLICATION		INK	
Sheetfed		UV	
Heatset		Conventional	
Coldset		Hybrid	
Packaging			
Coating		RECOMMENDED	
Metal		SUITABLE	
Continuous F.		NOT RECOMMENDED	

COLOUR
CONSTRUCTION
TYPE
SURFACE FINISH
SURFACE ROUGHNESS, RA
MICRO HARDNESS
STRETCH
NOMINAL THICKNESS

GAUGE LOSS
BOTTOM LAYER
PACKING & TENSIONING


Blue Cord Carcass Compressible Ground and polished $0,60-0,90~\mu m$ 65+/-3 IRHD <0,70~% at 500~N/5 cm 1,95~mm (ISO 12636) 1,69~mm (ISO 12636)

≤0,02 mm

Water/Solvent sealed

Conform to 0EM instructions

STRUCTURE



Printing surface Fabric ply

Close cell compressible layer

Cord ply

Sealed bottom fabric

CHARACTERISTICS

ADVANTAGES

Dimensional Stability

Virtually no sinking or stretching giving the blanket exceptional dimensional stability. After mounting no need for further retensioning thus leading to reduced down time.

New compressible layer coupled with the radial cord carcass improves durability, gives excellent shock absorption and rapid recovery. Resists solvent penetration, reduces the risk of de-lamination.

Microground Printing Surface

The specially formulated surface compound is specifically ground in order to ensure excellent ink transfer and dot reproduction on a wide range of paper/carton qualities.

Sealed Bottom Layer Gives added protection from water and chemical penetration.



Savatech, d.o.o. • Industrial Rubber Products and Tyres Škofjeloška c. 6 • 4000 Kranj • Slovenija • Tel + 386 (0)4 206 54 97 • Fax + 386 (0)4 206 64 00 info.print@sava.si • www.savatech.si • www.savaprint.com